

UNI-BOND INJECTION SYSTEM


EASY INSTRUCTIONS

STEP 1: Establish which tiles have hollow areas under them, mark these tiles with tape for future application.
Note: If the grout joint has deteriorated or cracked out, it will be necessary to re-grout these joints before applying the Uni-Bond.

STEP 2: Using a 3/8" drill with the 1/8th masonry drill bit, drill into the grout joint (**Minimum grout joint width is 1/8th inch.**) The depth you are drilling is the thickness of the tile. You will need 1 possibly 2 holes per tile. *USE CARE NOT TO DRILL INTO THE TILE.*



STEP 5: Clean any excess material immediately with a sponge and clean water.




STEP 3: Using a shop vacuum, clear away all loose debris in the holes and around the tile.



STEP 6: Carefully place weighted buckets of water on the reset tiles and allow a minimum of 24 hours curing.



STEP 4: Shake "Uni-Bond" well, and then cut the nozzle at the 1/8th" mark before inserting into the caulking gun. Put the tip of the nozzle directly into the drilled hole and surround the nozzle with a wet sponge. Now, hold the caulking gun straight up and down and inject with light pressure. While pumping, begin to lightly tap the tile with the rubber mallet. This helps the flow of "Uni-Bond".



STEP 7: Determine the color of your grout joints and fill the existing drilled holes with **Spectrum Caulk's** matching color and texture.

Tools Needed: 3 – 1/8th masonry drill bits, 3/8th" drill, caulking gun, grout sponge, rubber mallet, shop vacuum and several empty 5 gallon pails.

Manufactured by:



UNI-BOND

THE "CURE" FOR HOLLOW TILES!



The Quick and Easy Solution to loose and hollow Ceramic/Stone Tile Floors that have lost their bond to concrete or plywood substrate.

- UB** The Uni-Bond injection system is designed to re-adhere ceramic/stone tiles and pavers which have lost bond with the existing substrate.
- UB** Uni-Bond eliminates the time-consuming cleanup costs incurred by the conventional way of repairing. There's no dust, no odor and no disruption of re-tiling your floor, the floor is ready in virtually no time.
- UB** Uni-Bond eliminates tile die-lot matching problems as you do not have to tear out the existing tile.
- UB** Uni-Bond's unique elastomeric qualities allow for limited deflection (a common cause for loss of bond on concrete and plywood substrates) thus, eliminating a possible reoccurrence of the same problem.
- UB** Uni-Bond is non-toxic and odor-free single component adhesive that in it's uncured state, cleans up with water.
- UB** Uni-Bond will fit in an average caulking gun for dispersing and uses a high-pressure tube system for easy application.
- UB** Uni-Bond can be used on various flooring materials: ceramic tiles, quarry and brick pavers, marble and stone tiles, mexican tiles and most laminated floors.
- UB** Uni-Bond is an inexpensive, labor-saving fix.

MAKE YOUR FLOORS FEEL AND SOUND LIKE NEW AGAIN!

EASY INSTRUCTIONS ON BACK

Manufactured by: Spectrum Mfg. Corp. • www.specmfgcorp.com • 623-434-0097